

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2015/830



Article No.: 36-670-601
Print date 30.11.2017
Version 43.0

Raykon HL-4 Solid Lasur
Revision date 29.11.2017
Issue date 29.11.2017

EN
Page 1 / 8

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. product identifiers

Article No. (manufacturer/supplier): 36-670-601
Identification of the substance or mixture Raykon HL-4 Solid Lasur
Vario Solid Lasur
nussbaum / ceviz

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses:

Varnish / paint

Uses advised against:

Aware of any other information

1.3. Details of the supplier of the safety data sheet

Supplier (manufacturer/importer/only representative/downstream user/distributor)

P.A. Jansen GmbH u. Co., KG
Maler-Spezialprodukte Telephone: +49 2641 3897-0
Hochstadenstraße 22 Telefax: +49 2641 3897-28
D-53474 Bad Neuenahr-Ahrweiler Homepage: www.jansen.de

Dept. responsible for information:

laboratory
E-mail (competent person) info@jansen.de

1.4. Emergency telephone number

Emergency telephone number +49 2641 3897-53
Only available during office hours.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

The mixture is classified as not hazardous according to regulation (EC) No 1272/2008 [CLP].

2.2. Label elements

The product is classified and labelled according to EC directives or corresponding national laws.

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms

Hazard statements

No data available

Precautionary statements

No data available

contains:

No data available

Supplemental Hazard information (EU)

EUH208 Contains Fatty acids, C18 unsat, reaktion product with tetraethylenepentamine. May produce an allergic reaction.
EUH210 Safety data sheet available on request.

2.3. Other hazards

SECTION 3: Composition / information on ingredients

3.2. Mixtures

Product description / chemical characterization

Description

Hazardous ingredients

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2015/830



Article No.: 36-670-601
Print date 30.11.2017
Version 43.0

Raykon HL-4 Solid Lasur
Revision date 29.11.2017
Issue date 29.11.2017

EN
Page 2 / 8

Classification according to Regulation (EC) No 1272/2008 [CLP]

EC No. CAS No. INDEX No.	REACH No. Chemical name classification: // Remark	Wt %
918-481-9	01-2119457273-39 Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics Asp. Tox. 1 H304	50 - 70
203-572-1 108-32-7 607-194-00-1	01-2119537232-48 propylene carbonate Eye Irrit. 2 H319	1 - 1,5
245-018-1 22464-99-9	01-2119979088-21 2-ethylhexanacid, zirconium salt Repr. 2 H361d / Aquatic Chronic 4 H413	0,15 - 0,2

Additional information

Full text of classification: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

In case of inhalation

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

Following skin contact

Take off immediately all contaminated clothing. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

After eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

After ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

In all cases of doubt, or when symptoms persist, seek medical advice.

4.3. Indication of any immediate medical attention and special treatment needed

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

alcohol resistant foam, carbon dioxide, Powder, spray mist, (water)

Extinguishing media which must not be used for safety reasons:

strong water jet

5.2. Special hazards arising from the substance or mixture

Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage.

5.3. Advice for firefighters

Provide a conveniently located respiratory protective device. Do not allow water used to extinguish fire to enter drains, ground or waterways. Cool closed containers that are near the source of the fire.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Keep away from sources of ignition. Ventilate affected area. Do not breathe vapours.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.

Article No.: 36-670-601
Print date 30.11.2017
Version 43.0

Raykon HL-4 Solid Lasur
Revision date 29.11.2017
Issue date 29.11.2017

EN
Page 3 / 8

6.3. Methods and material for containment and cleaning up

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13). Clean using cleansing agents. Do not use solvents.

6.4. Reference to other sections

Observe protective provisions (see section 7 and 8).

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advices on safe handling

Avoid formation of flammable and explosive vapour concentrations in the air and exceeding the exposure limit values. Only use the material in places where open light, fire and other flammable sources can be kept away. Electrical equipment must be protected meeting the accepted standard. Product may become electrostatically charged. Provide earthing of containers, equipment, pumps and ventilation facilities. Anti-static clothing including shoes are recommended. Floors must be electrically conductive. Keep away from heat sources, sparks and open flames. Use only spark proof tools. Avoid contact with skin, eyes and clothes. Do not inhale dusts, particulates and spray mist when using this preparation. Avoid respiration of swarf. When using do not eat, drink or smoke. Personal protection equipment: refer to section 8. Do not empty containers with pressure - no pressure vessel! Always keep in containers that correspond to the material of the original container. Follow the legal protection and safety regulations.

Precautions against fire and explosion:

Vapours are heavier than air. Vapours form explosive mixtures with air.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSiVO). Keep container tightly closed. Do not empty containers with pressure - no pressure vessel! Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

Hints on joint storage

Keep away from strongly acidic and alkaline materials as well as oxidizers.

Further information on storage conditions

Take care of instructions on label. Store in a well-ventilated and dry room at temperatures between 5 °C and 30 °C. Protect from heat and direct sunlight. Keep container tightly closed. Remove all sources of ignition. Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

7.3. Specific end use(s)

Observe technical data sheet. Observe instructions for use.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limit values

No data available

DNEL:

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics

EC No. 918-481-9

DNEL long-term dermal (systemic), Workers: 300 mg/kg

DNEL long-term oral (repeated), Consumer: 300 mg/kg

DNEL long-term dermal (systemic), Consumer: 300 mg/kg

DNEL long-term inhalative (systemic), Consumer: 900 mg/m³

8.2. Exposure controls

Provide good ventilation. This can be achieved with local or room suction. If this should not be sufficient to keep aerosol and solvent vapour concentration below the exposure limit values, a suitable respiratory protection must be used.

Occupational exposure controls

Respiratory protection

If concentration of solvents is beyond the occupational exposure limit values, approved and suitable respiratory protection must be used. Use only respiratory protection equipment with CE-symbol including four digit test number. Observe the wear-time limits as specified by the manufacturer. Recommended respiratory protection articles : Inadequately ventilated workplaces and spraying procedures are necessary. Fresh air mask or short-time work combination filter A2-P2 are

Article No.: 36-670-601
Print date 30.11.2017
Version 43.0

Raykon HL-4 Solid Lasur
Revision date 29.11.2017
Issue date 29.11.2017

EN
Page 4 / 8

recommended.

Hand protection

For prolonged or repeated handling the following glove material must be used: NBR (Nitrile rubber)

Thickness of the glove material > 0,4 mm ; Breakthrough time (maximum wearing time) > 480 min.

Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recommended glove articles DIN EN 374

Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

Eye protection

Wear closely fitting protective glasses in case of splashes.

Protective clothing

Wear antistatic clothing of natural fibers (cotton) or heat resistant synthetic fibers.

Protective measures

After contact clean skin thoroughly with water and soap or use appropriate cleanser.

Environmental exposure controls

Do not allow to enter into surface water or drains. See chapter 7. No additional measures necessary.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties *

Appearance:

Physical state:

Liquid

Appearance:

Liquid

Colour:

refer to label

Odour:

characteristic

Odour threshold:

No data available

pH at 20 °C:

no information

Melting point/freezing point:

No data available

Initial boiling point and boiling range:

120 °C

Source: 1-methoxy-2-propanol

Flash point:

> 61 °C

Method: EN ISO 1523

Evaporation rate:

No data available

Flammability (solid, gas):

burning time (s):

No data available

Upper/lower flammability or explosive limits:

Lower explosion limit:

0,6 Vol-%

Method: literature value

Source: Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Upper explosion limit:

7 Vol-%

Method: literature value

Source: Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Vapour pressure at 20 °C:

0,6 mbar

Source: Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Vapour density:

No data available

Relative density:

Density at 20 °C:

0,89 g/cm³

Method: DIN 53217

Solubility(ies):

Water solubility (g/L) at 20 °C:

The study does not need to be conducted because the substance is known to be insoluble in water.

Partition coefficient: n-octanol/water:

see section 12

Article No.: 36-670-601
Print date 30.11.2017
Version 43.0

Raykon HL-4 Solid Lasur
Revision date 29.11.2017
Issue date 29.11.2017

EN
Page 5 / 8

Auto-ignition temperature:	231 °C Source: Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics
Decomposition temperature:	No data available
Viscosity at °C:	leicht thixotrop
Explosive properties:	No data available
Oxidising properties:	No data available
9.2. Other information	
Solid content (%):	33 Wt %
solvent content:	
Organic solvents:	67 Wt %
Water:	0 Wt %

SECTION 10: Stability and reactivity

10.1. Reactivity

10.2. Chemical stability

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7.

10.3. Possibility of hazardous reactions

Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions.

10.4. Conditions to avoid

Hazardous decomposition byproducts may form with exposure to high temperatures.

10.5. Incompatible materials

10.6. Hazardous decomposition products

Hazardous decomposition byproducts may form with exposure to high temperatures, e.g.: carbon dioxide, carbon monoxide, smoke, nitrogen oxides.

SECTION 11: Toxicological information

Classification according to Regulation (EC) No 1272/2008 [CLP]

No data on preparation itself available.

11.1. Information on toxicological effects

Acute toxicity

propylene carbonate

oral, LD50, Rat: 33520 mg/kg

dermal, LD50, Rabbit: > 2000 mg/kg

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics

oral, LD50, Rat: > 5000 mg/kg

Method: OECD 401

dermal, LD50, Rabbit: > 5000 mg/kg

Method: OECD 402

inhalative (vapours), LC50, Rat: > 4951 mg/l (4 h)

Method: OECD 403

skin corrosion/irritation; Serious eye damage/eye irritation

Toxicological data are not available.

Respiratory or skin sensitisation

Toxicological data are not available.

Specific target organ toxicity

Toxicological data are not available.

Aspiration hazard

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Aspiration hazard

Practical experience/human evidence

Other observations:

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2015/830



Article No.: 36-670-601
Print date 30.11.2017
Version 43.0

Raykon HL-4 Solid Lasur
Revision date 29.11.2017
Issue date 29.11.2017

EN
Page 6 / 8

Inhaling of solvent components above the MWC-value can lead to health damage, e.g. irritation of the mucous membrane and respiratory organs, as well as damage to the liver, kidneys and the central nerve system. Indications for this are: headache, dizziness, fatigue, amyosthenia, drowsiness, in serious cases: unconsciousness. Solvents may cause some of the aforementioned effects through skin resorption. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and/or absorption through skin. Splashing may cause eye irritation and reversible damage.

Overall Assessment on CMR properties

The ingredients in this mixture do not meet the criteria for classification as CMR category 1A or 1B according to CLP.

Remark

There is no information available on the preparation itself .

SECTION 12: Ecological information

overall evaluation

Classification according to Regulation (EC) No 1272/2008 [CLP]

There is no information available on the preparation itself .

Do not allow to enter into surface water or drains.

12.1. Toxicity

propylene carbonate

Daphnia toxicity, EC50, Daphnia magna: > 1000 mg/l (48 h)

Algae toxicity, ErC50: > 900 mg/l

Bacteria toxicity: 25619 (16 h)

Method: DIN 38412

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Fish toxicity, LC50, Oncorhynchus mykiss (Rainbow trout): > 1000 mg/l (96 h)

Daphnia toxicity, EC50: > 1000 mg/l (48 h)

Algae toxicity, ErC50: > 1000 mg/l

12.2. Persistence and degradability

propylene carbonate

: 85 % 83,5 - 87,7 % (29 d)

12.3. Bioaccumulative potential

Toxicological data are not available.

12.4. Mobility in soil

Toxicological data are not available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Other adverse effects

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Appropriate disposal / Product

Recommendation

Do not allow to enter into surface water or drains. This material and its container must be disposed of in a safe way. Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

List of proposed waste codes/waste designations in accordance with EWC

080111 Waste paint and varnish containing organic solvents or other dangerous substances

packaging

Recommendation

Non-contaminated packages may be recycled. Vessels not properly emptied are special waste.

SECTION 14: Transport information

This mixture is not classified as dangerous according to international transport regulations (ADR/RID, IMDG, ICAO/IATA).

14.1. UN number

No data available

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2015/830



Article No.: 36-670-601
Print date 30.11.2017
Version 43.0

Raykon HL-4 Solid Lasur
Revision date 29.11.2017
Issue date 29.11.2017

EN
Page 7 / 8

14.2. UN proper shipping name

14.3. Transport hazard class(es)

No data available

14.4. Packing group

No data available

14.5. Environmental hazards

Land transport (ADR/RID)

No data available

Marine pollutant

No data available

14.6. Special precautions for user

Transport always in closed, upright and safe containers. Make sure that persons transporting the product know what to do in case of an accident or leakage.

Advices on safe handling: see parts 6 - 8

Further information

Land transport (ADR/RID)

tunnel restriction code

-

Sea transport (IMDG)

EmS-No.

No data available

Air transport (ICAO-TI / IATA-DGR)

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

National regulations

Restrictions of occupation

Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers. Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).

15.2. Chemical Safety Assessment

For the following substances of this preparation a chemical safety assessment has been carried out:

EC No. CAS No.	Chemical name	REACH No.
918-481-9	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics	01-2119457273-39
203-572-1 108-32-7	propylene carbonate	01-2119537232-48
245-018-1 22464-99-9	2-ethylhexanacid, zirconium salt	01-2119979088-21

SECTION 16: Other information

Full text of classification in section 3:

Asp. Tox. 1 / H304

Aspiration hazard

May be fatal if swallowed and enters airways.

Eye Irrit. 2 / H319

Serious eye damage/eye irritation

Causes serious eye irritation.

Repr. 2 / H361d

Reproductive toxicity

Suspected of damaging the unborn child.

Aquatic Chronic 4 / H413

Hazardous to the aquatic environment

May cause long lasting harmful effects to aquatic life.

Abbreviations and acronyms

ADR

European Agreement concerning the International Carriage of Dangerous Goods by Road

WEL

occupational exposure limit value

CAS

Chemical Abstracts Service (division of the American Chemical Society)

CLP

Regulation (EC) No 1272/2008 on the classification, labelling and packaging of substances and mixtures

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2015/830



Article No.: 36-670-601
Print date 30.11.2017
Version 43.0

Raykon HL-4 Solid Lasur
Revision date 29.11.2017
Issue date 29.11.2017

EN
Page 8 / 8

CMR	Substances classified as Carcinogenic, Mutagenic or toxic for Reproduction
DIN	German institute for standardization /German industry standard
DNEL	Derived No-Effect Level (REACH)
EINECS	European Inventory of Existing Commercial Chemical Substances
IATA	International Air Transport Association
IMDG Code	International maritime code for dangerous goods
LC50	Lethal concentration, 50 percent
LD50	Lethal dose, 50 percent
OECD	Organization for Economic Cooperation and Development
PBT	Persistent, bioaccumulative and toxic substances
PNEC	Predicted No-Effect Concentration (REACH)
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Regulation on the international carriage of dangerous goods by rail
TRBS	Technical rules Operational safety
VOC	Volatile organic compounds
vPvB	very persistent, very bioaccumulative

Data sources:

Data arise from reference works and literature.

Further information

Classification according to Regulation (EC) No 1272/2008 [CLP]:

Classification procedure:

Physical hazards: On basis of test data.

Health and environmental hazards: Calculation method.

The information supplied on this safety data sheet complies with our current level of knowledge as well as with national and EU regulations. Without written approval, the product must not be used for purposes different from those mentioned in chapter 1. It is always the user's duty to take any necessary measures for meeting the requirements laid down by local rules and regulations. The details in this safety data sheet describe the safety requirements of our product and are not to be regarded as guaranteed attributes of the product.

* Data changed compared with the previous version